



RIKEN KEIKI

RIKEN GAS DETECTOR HEAD

GD-A80 series

RoHS
compliant

CE



【Combustible gases】

GD-A80



【Toxic gases】

GD-A80V

Connect with indicator unit



RM-5000 series



RM-6000 series

Features

- Explosion class Exd IIC T4 Gb
- Sample draw, aspirating type available
- Small, rugged

RIKEN KEIKI Co.,Ltd.

Specifications

Model	GD-A80 ※1,2	GD-A80V ※1,2	GD-A80S ※1,2	GD-A80N ※1,2	GD-A80-70 ※1
Detection principle	Catalytic combustion/New ceramic type	Semi-conductor type	Hot wire semi-conductor type	Thermal conductivity type	Catalytic combustion type
Gas to be detected	Combustible gases	Combustible/toxic gases	Combustible/toxic gases	Combustible/inert gases	Combustible gases
Detection range	Diffusion type				
Transmission cable	CVV 1.25mm ² or 2mm ² 4-core	CVVS・1.25mm ² or 2mm ² ・3-core	CVVS 1.25mm ² or 2mm ² 4-core		Heat-resistant wire 1.25mm ² or 2mm ² 4-core
Transmission distance	Depends on indicator				
Power supply	Supply from indicator				
Operating temperature	-20 ~ +53°C(at a constant condition)				-40 ~ +70°C (at a constant condition)
Operating humidity	Below 95%RH (Non-condensing)				
Structure	Wall mounting type				
External dimensions/Weight	Approx. 78 (W) x 154 (H) x 105 (D) mm (projection portions excluded) Approx. 1.0kg				
Explosion-proof	Flame-proof enclosures (ATEX Exd IIC T4 Gb)				

※1. Sample drawing type available (external pump unit excluded)

※2. Aspirator type available

Standard accessories

- Fix bracket
- Hex driver (2mm)
- Hex driver (4mm)

Optional accessories

- Drip-proof cover
- Calibration cap
- Silicon removal filter: SI-5
- Charcoal filter: CF-8394



RIKEN KEIKI Co., Ltd.

2-7-6 Azusawa, Itabashi-ku, Tokyo 174-8744, Japan
Phone : +81-3-3966-1113
Telefax : +81-3-3558-9110
E-mail : intdept@rikenkeiki.co.jp
Web site : <http://www.rikenkeiki.co.jp>



TAIYO GASES Co., Ltd.

1768 Thai Summit Tower 27th Floor, New Phetchaburi Road,
Bang Kapi, Huai khwang, Bangkok 10310
Tel : 02-260-2691
Email : riken@taiyogases.com